Air King Ventilation Products®

SPECIFICATIONS

AR SERIES

RANGE HOODS

180 CFM/7.0 Sones @ 0.10" WG. Horizontal, 180 CFM/7.5 Sones @ 0.10"WG. Vertical, 120 Volts, 2.1 amps, 60hz



AR SERIES

- **Dimensions**
  Overall bottom projection - 18 3/8"
  Overall top projection -12"
  Height - 6". Available widths: 30" & 36"
- **Hood Body**
  23 gauge cold rolled steel, auto welded, coated with a baked enamel finish.
- **Motor**
  2 speed, single coil, thermally protected, permanently lubricated. Rated 120 volts, 60 hz., 2.1 amps.
- **Lighting**
  Single 60 watt cook light capacity (bulb not included).
- **Ducting Options**
  Vertical ducting: 7" round (duct collar built into hood).
- **Fan Blade**
  One piece polymeric, electronically balanced blade. 6 5/8" diameter with 5 paddles.
- **Electrical connection**
  Hood top - 7/8" electrical knockout.
  Hood back - 7/8" electrical knockout.



- **Filters**
  UL rated, class 2 filter.
  Grease Filter: RF35 - 8 7/8"x10 3/8" (included).
- **Available Finishes**
  White, Biscuit, Almond, Black & Stainless Steel.

PERFORMANCE

	Static Pressure (inches of w.g.)								HVI Sones @ .1 SP	Fan Speed RPM	Power Watts
	0	0.05	0.1	0.125	0.15	0.2	0.25	0.3			
Air Flow - CFM	203	191	180	167	148	124	101	82	7.5	2973	87

PROJECT		ARCHITECT	
LOCATION		ENGINEER	
CONTRACTOR		SUBMITTED BY	DATE

FAN NUMBER	MODEL NUMBER	CFM	IN W.G.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS

c UL us

2100 HVI CERTIFIED™

U.S.: 820 Lincoln Drive
West Chester, Pennsylvania 19380-4466
Tel: (610) 692-7400 • 877-304-3785
Fax: (610) 696-8048

Canada: 110 Glidden Road
Brampton, Ontario L6T 2J3
Tel: (905) 456-2033
Fax: (905) 456-1015

Downloaded from www.Manualslib.com manuals search engine